

# Quatro® Dielectric Footwear

ASTM F1117

Skellerup has been the leader in the design and manufacture of high-quality, genuine, hand-crafted protective footwear for over 75 years. The Quatro® name is renowned for its durability, comfort, traction, and performance. When the job and safety requirements call for ASTM F1117 compliant footwear, count on Skellerup's certified range of Quatro® Dielectric boots and overshoes.

## Proven Reliability and Performance



## PROTECTIVE FOOTWEAR



### FQD8 SERIES

ASTM F2413 M I/75/C/75  
PR  
ASTM F1117 20kV  
Sizes 5-15 | Height 15"

Regular Boot



### FQD9 SERIES

ASTM F2413 M I/75/C/75  
PR  
ASTM F1117 20kV  
Sizes 5-15 | Height 15"

Thermal Boot



### FQD5 SERIES

ASTM F2413 M I/75/C/75  
PR  
ASTM F1117 20kV  
Sizes 4-15 | Height 11"

Thermal Boot



### FRO3 SERIES

ASTM F1117 20kV  
Sizes 7-17

Slip On Overshoe



### FRO4 SERIES

ASTM F1117 20kV  
Sizes 7-17

2 Buckle Overshoe



### Skellerup Footwear USA

1890 Lyndon Boulevard  
Falconer, NY 14733

(844) 822-2100

info@quatrodielectricfootwear.com

[quatrodielectricfootwear.com](http://quatrodielectricfootwear.com)

v.2024-03

## Know the Difference

### EH vs DIELECTRIC FOOTWEAR

**ASTM F2413 EH**  
(Electric Hazard)

- 18 kV
- Dry Test
- 1 Minute Test
- Sole Unit Only
- Lot Testing

**ASTM F1117**  
(Dielectric)

- 20kV
- Wet Test
- 3 Minute Test
- Entire Boot (3" from top)
- Every Boot Tested

Check your footwear label to know what you are wearing.